



Also available in:



### STEEL ROSE EYES

CODE	SS CODE	A	B	C	D	E	F	G	H	STRUT ROD DIA
RE8	SSRE8	M6	30	20	6	11	6.75	5	9	6 & 8mm
RE10	SSRE10	M8	36	24	8	14	9	5	12	10mm
RE12	SSRE12	M10	43	28	10	17	10.5	6.5	14	14mm

### KEY

LABEL	PART	DESCRIPTION
A	INTERNAL THREAD	Where the end fitting screws onto the strut
B	FITTING LENGTH	From the centre of the eye to the end of the fitting
C	OUTER RADIUS	Outer eye radius
D	EYE HOLE DIAMETER	The measurement of the internal diameter of the eye
E	SHOULDER WIDTH	Width of the shoulder
F	THICKNESS	Eye thickness
G	SHOULDER HEIGHT	Height of the shoulder
H	SPHERE PROFILE	Width of the sphere profile

### ADVICE ON USING END FITTINGS

- Where possible use ball joints to avoid side loading
- Ensure end fittings are fully screwed to the strut
- Ensure end fittings are in line to avoid side loading
- When using ball joints ensure the stud is fixed to the socket and the clip is in position
- Ensure the gas strut matches the chosen end fittings

